



MOKO SMART

# Durable | Ruggedized

**M3 mini**

Asset Tracking Tag



The M3 mini, a high-performance Bluetooth asset tracking tag, is designed for industrial applications, offering exceptional structural and installation advantages. Its moderate size allows for easy deployment on a wide range of industrial assets.

Equipped with a large 2600mAh battery, this product boasts an exceptionally 8+ years lifespan. Additionally, its built-in magnet provides powerful adhesion to metal surfaces, ensuring the device remains securely in place.


## Magnetic Suction Support



① Double-sided tape



② Screws



③ Magnetic suction

## Key selling points



Magnetic  
adsorption



IP67  
waterproof



Reinforced  
industrial design




8+ years  
battery life

## General specs

|                        |   |
|------------------------|---|
| Connectivity:          | BLE 5.0   |
| Dimensions:            | 94.6*51.7*22.8mm                                      |
| Color:                 | Black   |
| Material:              | PC + ASA  |
| Weight:                | 30g   |
| IP rating:             | IP67  |
| Sensor:                | Accelerometer sensor<br>Hall effect sensor (Optional) |
| Battery capacity:      | 2600mAh   Replaceable battery                         |
| Battery lifespan       | 8+ years*   |
| Operating temperature: | -30°C to 80°C   |

|                     |   |
|---------------------|---|
| Transmission range: | 150m (Open area without obstacles)                          |
| Installation:       | Screw   Sticker   Zip Tie<br>Magnetic adsorption (Optional) |
| Certification:      | FCC   CE   RoHS   REACH   Bluetooth                         |



## More than location




### Constructions

- Geo-fence alerts
- Asset anti-theft alarm
- Equipment managements



### Warehouse

- Improve utilization of tools and equipments
- Prevent the use of equipment overdue maintenance or calibration
- Optimize stock levels eliminate shortages



### Manufacturing

- Raw material tracking
- Turnover box utilization monitoring

\*Lifespan estimated based on standard asset tracking scenario under 25°C conditions, (0dBm Tx Power | 1000ms ADV interval | iBeacon advertisement)